Dark Energy Camera and Survey

Response to NOAO Announcement of Opportunity for Blanco Instrumentation Partnership

Sample of ~30,000 clusters out to redshift z≈1 and overlap with SPT Sample of ~30,000 clusters out to redshift z≈1 and overlap with SPT Supplemental and

Measurements of weak lensing shear-shear and galaxy-shear correlations for 10-20 galaxies per arcmin² and 5000 deg² of sky

68% C.L. contours on w and $\Omega_{\rm DE}$ from shear-shear correlations (read), from galaxy-shear correlations (green), and from the joint constraint (blue). (from Hu, Frieman & Sheldon: cf. Hu & Jain 2003)

Galaxy Angular

Power Spectrum

Measurement of angular power spectrum for \sim 300 million galaxies over 5000 deg², binned in photometric-redshift shells out to $z\sim$ 1.


Estimate 1σ constraint $\sigma_{w} \sim 0.1$ on constant w models.


Type la Supernovae

Weak

Lensing

Light curves of ~ 2000 Type Ia SNe at $z \approx 0.3$ -0.8 over 40 deg²





Projected constraints on w and $\Omega_{\rm M}$ (flat cosmology) from the SN Ia sample only (red), combined with 2dF (blue, left), or combined with the DES+SPT clusters (blue, right). The right-hand curves in each panel marginalize over $\Omega_{\rm M}$. Follow-up spectroscopy assumed. (figures from Smith, Miknaitis & Suntzeff)


Teles

of the Blanco telescope

showing the cage holding th Dark Energy Camera


Telescope, Cage, and Camera

The existing 4m Blanco telescope at Cerro Tololo already provides imaging capabilities at its prime focus. We propose to replace the entire cage with an imager that will be over 10 times more powerful than the existing imager in the i and z bands.



Focal Plane Layout

Our reference design consists of a mosaic of 62 CCDs covering a hexagonal FOV, with an effective area of 3 sq degrees for tiling the sky





Photometric Redshifts

We require accurate galaxy photometric redshifts to z~1. Use g, r, i, z filter bands to be sensitive to the 4000Å break over the redshift range of interest.


We require large format CCDs with high QE in the near IR (~1 $\mu m)$. Our reference design uses LBNL developed thick (250 $\mu m)$, fully depleted 2K x 4K devices.

Typical QE curves of LBNL thick, high resistivity devices (red) which show higher QE in the red.

Dirbe map of galactic dust


with DES area

outlined in green



Spectrum of a red elliptical galaxy at z = 0, 0.5, and 1, with the 4000Å break feature marked. Also shown are the g, r, i, z filter bandpasses.





Photometric calibration error after 3 and 5 yrs.
The scale spans the range from -0.2 to 0.2 mag

Paths of constant airmass for one tiling Monte Carlo simulations of photometric redshift accuracy for 0.5L* and 2L* red cluster galaxies. Photo-z errors are < 0.03.

Dark Energy Camera and Survey

Fermilab, Univ. of Illinois, Univ. of Chicago, LBNL, Cerro-Tololo Inter-American Observatory Survey Strategy

We plan to cover 5000 sq deg with tiling hexagons in the South Galactic Cap, with 4000 sq deg of overlap with the South Pole Telescope 5Z cluster survey. Our reference survey area also includes equatorial regions that overlap existing SDSS and VLT redshift surveys. Historical weather data have been analyzed and indicate that we will be able to complete the survey in 5 years with a 3 sq deg FOV camera.